





ARKITEK


INDIVIDUAL AND EXECUTIVE DESKS




DESKS WITH RETURN SUPPORTED BY PEDESTAL UNIT




EXECTURIVE DESK SUPPORTED BY BLOCK STORAGE UNIT




TWIN DESKS WORKSTATION - MEETING TABLES - WIDTH - 140/160 cm




MEETING TABLES - WIDTH - 120 cm





MEETING TABLES




DESK SUPPORTED BY SPINE STORAGE UNIT















RECTANGULAR DESKS






RECTANGULAR DESKS










BENCH DESKING (PROGRESSIVE SYSTEM)







TWIN DESKS WORKSTATION





Single desks



Bench desks



■ DESK-TOP FINISHES

MFC (19 mm)



antifingerprint

Compact Laminate (13 mm)



Laminated security glass (5+5/6+6 mm)



Tempered security glass (10 mm)





■ FRAME

Moulded aluminium legs and extruded aluminium beams. Five different finishes: Silver, White or Black coating, Polished or Chrome



White coating



Silver coating







■ LEG SUPPORTS

Moulded aluminium leveller. Chrome.

Each leveller includes anti-skid pad.





Leveller - desk height: 74,5 cm


■ ELECTRIFICATION SYSTEM

Full length cable channel with large capacity for cables. Easy access to the

cables from the worktop.







40cm Channel for individual use 160, 180, 200 and 220cm desks

■ CABLE ACCESS DESKS

Q WIRING ACCESS	R WIRING ACCESS	
MAXIMUM OPENING: 110°	MAXIMUM OPENING: 180°	
 Black die-cast aluminium frame Aluminum injected lid with soft-close retention system Dimensions: 30,5 x 11,5 cm 	 Melamine lid of the same finish as the surface Black Bristle Brush Aluminum injected lid with soft-close retention system Complete opening in 180° by means of hinges. Dimensions: 30,5 x 11,5 cm 	



MATERIALS

Maximum use of materials to eliminate and minimize scraps. Use of recyclable and recycled materials in those components that do not affect the functionality and durability.

77.47%



PRODUCTION

Maximum optimization of energy use. Minimal environmental impact. Last generation technological systems. Zero discharge of wastewater. No VOC coatings. Processes free of heavy metals, phosphates, OC and COD.

ALUMINIUM, STEEL & W00D



TRANSPORT

Detachable systems. Volumes that facilitate the optimization of space. Maximum reduction of energy consumption by transport.

100% RECYCLABLE PACKAGE AND THINNER FREE



USE

Quality and warranty. Long lasting. Replacements available.

EASY TO CLEAN AND MAINTAIN



DISPOSAL

Waste reduction. Supplier-manufacturer packaging reuse system. Components are easy to be separated. Inks in packaging are water-based, without solvents.

98,54%

CERTIFICATES AND REFERENCES

The different programmes get points in different environmental categories to get the LEED certificate (sustainability, material and resources, water, energy and atmosphere, inner environment quality, innovation and design).





ECODESIGN Certificate



ISO 9001 Certificate



ISO 14001 Certificate



California 93120



ACTIU TECHNOLOGY PARK Leadership in Energy & Environmental Design LEED® Gold certified 2011 • LEED® Platinum certified 2011

STANDARDS

ARKITEK has passed tests done in our technical department as well as the tests done in AIDIMA the Technological Institute for furniture. The tests correspond to UNE standards and office desks:

- UNE: EN 527-1:2011. Office Furniture. Desks. Part 1: Dimensions.
- UNE: EN 527-2:2017. Office Furniture. Desks. Part 2: Requirements for safety, resistance and durability.
- UNE: EN 15372:17. Office Furniture. Strength, durability and safety. Requirements for domestic use desks. Office Furniture. Desks.
- UNE: EN 1730:13. Furniture. Tables. Test methods for the determination of stability, strength and durability.